

DESIGN & INTEGRATION LAMINATOR



Laminator

Standard Specifications:

- Lamination of any material
- Non marking donuts
- Pneumatic Friction Clutch
- Tilt-Lock Chucks
- Edge guide
- Solid Construction
- Powered In feed/ Out feed
- Glass thickness quick adjustment

Options Available:

- Width Slitter → Cut the film's width to match your glass.
- Re-winder → Used to rewind a liner or width slit film.
- Second Re-winder → Used when both width slitting and removing a liner.
- Strip Bar → Used to Remove a Liner.
- Anti Static Bar → Removes static from the film.
- Cross Cut Knife → Automatically cuts the film between two pieces of laminated glass.
- Top and Bottom Lamination
- Heated application of film

Ordering Information

Reference Model: Lamina-2006

Specify: Height from Floor, Smallest glass sizes, and largest glass sizes, Film types, options required

Delivery: 10-12 Weeks

- Glass Handling
- Glass Lamination
- Liquid Lamination
- PVB Equipment
- Steel Handling
- Lazer Welding
- Presses
- Conveyors
- Plate Saws
- Packing Equipment
- Lifts
- Glass Carts
- Storage Racks

905-669-8497

sales@designintegration.com

WWW.GLASSMACHINE.CA