



DESIGN & INTEGRATION

Phone 905-669-8497 • Fax: 905-669-3607

E-mail: Sales@designintegration.com

LIQUID LAMINATION LINE



WWW.GLASSMACHINE.CA

UV OVEN



System Specifications:

- Comes in 30' and 20' models
- Belt Conveyor
 - o 86" Wide
 - o Guided along the entire length with V Guides
 - o UV Stable Belt withstanding 200°F
 - o Bottom roller supports under the belt to reduce tension and extend the life of the belt
- Sturdy Design
 - o Solid 8" Channel Base Frame to maintain flatness and rigidity
 - o Solid flat bed to support the belt
- Hydraulic lifts on Light portion easy maintenance
 - o Lights held at a minimum of 6" from the belt
 - o UV Meter with Limits and Digital Display
 - o UV Level Adjustments
 - o Power Input Display on Electronic Ballasts
 - o Side panels swing up for easy access to light fixtures
- Line speed is adjustable
- Highly recommended In feed conveyor and Out feed conveyor

Requirements:

240V, 480V, 575V, 3PH

Floor Space: 100" x 33' or 23'

Ordering Information

Reference Model: 06-1512-20'

Reference Model: 06-1512-30'

Delivery: 10-12 Weeks